

EXCLUSIVE BRANDS *in stock*

MACKENZIE
INDUSTRIAL & SAFETY
FICODIS
VARCO VENDING

AGL65ALCA

Extreme pressure grease - AGL 65 AL

400G cartridge
Low-viscosity mineral oil, complex aluminium thickener. Resistant to water. Temperature resistance. Excellent stability to impact and vibrations. Resistant to corrosion and oxidation. High-performance anti-wear and extreme pressure. Authorized for use in incidental contact with food. (N° 147547)



LionProFoam

750 ml. Gun version.
LPF0001
Use: Doors and windows
Application temperature: min 5 deg.

LPF0004
Usage: All seasons
Application temperature: down to -25 deg



DEMOLUBA1

Silicone-free mould release agent - DEMOLUB

520/400 mL
Colourless anti-stick mould agent free of silicone, chlorine solvents and HCFC. For operations on cold or hot moulds. Can be applied on non-porous substrates. No residue and does not mark parts.



DGTA3

MoS2 lubricating- penetrating oil - DEGRIPPANT

800 mL
Lubricating penetrating oil with Molybdenum Bisulphide with very high penetration properties. Prevents subsequent seizure.



DEMO740NA2

Plastic mould release agent - DEMOPLAST 740

650/500 mL
Anti sticking colourless fluid mould agent with a synthetic oil base, guaranteed free of chlorine solvents and HCFC. With a paintable silicone oil base. For operations on cold or hot moulds. Can be applied on non-porous substrates. No residue and does not mark parts.



DRYPROTECA2

Long-lasting wax protective fluid - DRY PROTEC

650 mL
Ensures a very fine wax film, dry to the touch. Blue tint. Highly moisture resistant, water repellent effect in the event of condensation. Does not run and prevents clogging of moulds. Dry to the touch after a few minutes.



PERF80A2

Synthetic fluid - PERF 80 NF

650 Gr

Fluorinated oil for extreme applications. Compatible with all types for metal. Long duration lubrication at very low or very high temperatures, as well as in corrosive chemical conditions. MOSH-MOAH and POSH free lubricant. Registered by NSF International, in category H1= authorized for use in incidental contact with food. (N°130671).



KL9HPULVE

Ecofriendly aqueous degreasing cleaner - KL 9 H

Ready for use. Renewable raw material-based. V.O.C free, petroleum-based solvent free, chlorine free, EDTA free, glycol free. MOSH-MOAH and POSH free cleaner. Registered by NSF International, in category A1 = authorized for use in incidental contact with food. (N°162092).



GALVASUNA2

Glossy cold galvanising agent - GALVASUN

500 mL

Aluminium-based for the long-term protection of all metals. Good resistance at aggressive temperatures. Temperature resistance: 400°C. Drying time for handling: 1 hour.



OG844A3

Gear and cable grease - OG 844

500 mL

Extreme pressure mixture containing a high percentage of molybdenum disulphide. Mineral-based oil. Thickener: aluminium complex. Insoluble in water.



MULTIB1 / MULTICA

EP2 multi-purpose grease - MULTI TP

High pressure resistance.
Extremely stable during work and in storage.
Lithium soap thickener.
Available in 400G cartridge and 1 L



SCA200CA

Extreme pressure calcium sulfonate grease - SCA 200

400 Gr

High tech grease suitable for the lubrication of mechanical parts working under high loads and in humid surroundings.



TEREFL

Tapping, drilling and machining fluid - TEREBOR

125 Gr

Low-viscosity lubricant for drilling, tapping, and machining. Blue colour.



NB25A1

Boron nitride coating - NB 25

400 mL

Dry film that can protect surfaces up to 1000°C. Guaranteed silicone-free and without chlorine solvents. No smoke or clogging of nozzles.



TOP10A2

Multi-purpose Lubricant - Penetrating oil - TOP TEN

650 mL

Penetrates the smallest gaps of the metal. Releases heavily corroded mechanisms. Lubricates small mechanisms. Displaces water. Protects against oxidation and displaces moisture from electric and electronic circuits and devices.



VGCUTT77A2

Drilling and tapping Ecofriendly water-based lubricant - VG CUT 77

650 mL

Ready-to-use aqueous fluid without V.O.C. non-flammable, V.O.C free Vegetable polymer-based. Odourless. No smoke emissions. Compatible with all types of metal, including copper and its alloys. Easy to degrease.



VEGA908A2

Ecofriendly lubricant for chains and cables - VEGA 908

650 mL

Without safety labelling. Renewable raw materials-based, used for lubrication in moist conditions. Smooth and adherent with good anti-wear qualities. Strong penetrative properties for homogeneous spreading of lubricant up to the centre of link shafts. Contains 100% USDA certified biobased content.



3790A2 / 3790CA

Marine grease - GRAISSE 3790

Available in 400G cartridge and 650/400ML
Totally insoluble in cold, hot or sea water as well as in steam these properties enable to use it for lubrication of immersed or under severe water spray working equipment's. Highly adhesive and stringy.



**MACKENZIE
INDUSTRIAL & SAFETY**
FICODIS

VARCO VENDING

CHATHAM
519 354-7844

mackenzie-is.com

